

<b>Camera</b>		
<b>Camera</b>	<b>Image Sensor</b>	1/4" 720P CMOS
	<b>Effective Pixels</b>	1280 (H)x720(V)
	<b>WDR</b>	Digital WDR
	<b>Noise Reduction</b>	3D DNR
	<b>Day/Night control (IR-</b>	Auto(ICR) / Color / Black&White
	<b>Motion detection</b>	Supports
	<b>Privacy Masking</b>	Supports, 4 areas
	<b>IR distance</b>	30m
<b>Lens</b>	<b>Focal Length</b>	2.8mm
	<b>Max Aperture</b>	F2.4
	<b>Focus control</b>	Fixed
	<b>Angle of View</b>	55°
<b>Video</b>	<b>Encode</b>	H.264 Main/Baseline profile
	<b>Resolution</b>	Main Stream: 720P (1280x720)+ VGA (640x480) Sub Stream: VGA (640x480) + QVGA (320x240)
	<b>Video Bitrates</b>	32Kbps ~ 6144Kbps
	<b>Video Frame Rate</b>	25fps@720P
	<b>Image snapshot</b>	Supports
	<b>Dual video stream</b>	Supports
<b>Network</b>	<b>Ethernet</b>	RJ-45 (10/100Base-T)
	<b>Network Protocol</b>	HTTP, FTP, TCP/IP, UDP, SMTP, DHCP, NTP, UPNP, RTSP, Onvif,
	<b>Web browser</b>	Windows: IE/Firefox/Chrome, Mac: Safari/Chrome
	<b>Smart Phone</b>	FDT view App, IOS: iPhone+IPad, Android: smartphone+pad
	<b>Wifi</b>	WiFi (802.11b/g), 2.4G only, supports WEP/WPA-PSK/WPA2-PSK encryption
	<b>P2P</b>	Supports
	<b>Max. User Access</b>	3 users (Main stream) + 3 users (Sub stream)
<b>General</b>	<b>Power Supply</b>	DC 12V/2A
	<b>Hard Reset</b>	Supports
	<b>Power Consumption</b>	<6W
	<b>Working Environment</b>	-10℃~+55℃,10%~90% RH
	<b>Dimensions</b>	255x125x170mm
	<b>Weight</b>	1kg